

Color Chart

VINYL COLOR CHIP

Vinyl Color Chips can be broadcasted into KRETUS Top Shelf® Epoxy, Polyaspartic, Polyurethane HS, and Urethane Polymer Concrete to create beautiful seamless floors.



Chip Size

Standard: 1/4" (pictured)

Premium: 1/32", 1/16", 1/8", 1/2" and 1"

Coverage Rate			
1/32" Chip	1/16"-1/8" Chip	1/4"-1/2" Chip	1" Chip
2-4 sf./lb.	3-6 sf./lb.	5-10 sf./lb.	8-12 sf./lb.

General Mixing Guide

Ensuring uniform color: Check that product batch numbers are the same. Different batch numbers can produce slight variance in color. If different batch numbers, box product together and blend thoroughly before mixing product with other components. Always test application on site.

Broadcasting: To keep chips from disappearing into coating, allow coating to cure for 10–15 minutes. Then broadcast chips according to desired look. Coverage rates vary depending on customer preferences and application techniques.

Colors are shown as examples only. KRETUS® does not manufacture or distribute color quartz and color chip. Color and availability depend on the customer's chosen manufacturer and distributor.

DISCLAIMER: The information contained in this document is intended for use by KRETUS GROUP® qualified and trained professionals. This is not a legally binding document and does not release the specifier from his/her responsibility to apply materials correctly under the specific conditions of the construction site and the intended results of the construction process. The most current valid standards for testing and installation, acknowledged rules of technology, as well as KRETUS GROUP® technical guidelines must be adhered to at all times. The steps given in this document and other mentioned documents are critical to the success of your project.