



THOUGHTFULLY DESIGNED CONCRETE COATINGS

**Color Chart**

**POLY COLORANT**

Combine KRETUS® Poly Colorant packs with clear KRETUS® Polyaspartic and Polyurethanes for long-lasting color.



**General Mixing Guide**

Ensuring uniform color: Check that product batch numbers are the same. Different batch numbers can produce slight variance in color. If different batch numbers, box product together and blend thoroughly before mixing product with other components. Always test application on site.

Mixing application: Premeasure components before combining. Add Poly Colorant to Part A and mix for 1 minute. Add Part B and mix for 2 minutes. Total mixing time = 3 minutes.

Mix Ratio Chart		
Kit Size (gal.)	Kit Size (oz.)	Poly Colorant (oz./kit)
1.25	160	10
1.5	192	12
2	256	16
5	640	40
6	768	48
10	1,280	80
100	12,800	800

Colors shown are approximate. Resin and hardener selection, substrate, mix ratio, application technique, ambient temperature, and relative humidity may affect color. Sold as colorant packs only. To order a pre-blended color base or custom color, fill out KRETUS® Special Order form available at [kretus.com/project-planning](http://kretus.com/project-planning). Additional fees apply.

DISCLAIMER: The information contained in this document is intended for use by KRETUS GROUP® qualified and trained professionals. This is not a legally binding document and does not release the specifier from his/her responsibility to apply materials correctly under the specific conditions of the construction site and the intended results of the construction process. The most current valid standards for testing and installation, acknowledged rules of technology, as well as KRETUS GROUP® technical guidelines must be adhered to at all times. The steps given in this document and other mentioned documents are critical to the success of your project.