KRĒTUS

THOUGHTFULLY DESIGNED COATINGS

Color Chart

METALLIC


IVORY*


CARBON


BLACK


ANTIQUE SILVER


DARK GRAY


STERLING


CHERRYWOOD


SUNSET GOLD


CALIFORNIA GOLD


NEW COPPER


SEDONA


CABERNET


VIOLET


OLIVE


FOREST GREEN


JADE GREEN*


SKY BLUE


DARK BLUE


SILVER GLITTER*


GOLD GLITTER*

Neon Accent Colors


HOT PINK*


RADIANT RED*


ORANGE BLAZE*

HIGHLIGHTER YELLOW*


LIME GREEN*


ELECTRIC BLUE*

KRĒTUS

THOUGHTFULLY DESIGNED COATINGS

BEST PRACTICES

- **Appearance:** Colors are approximate. Final look may vary based on product, substrate, mix ratio, technique, climate, and location.
- **Batching:** Use the same batch number for consistent color. If batches differ, mix them together until the color is uniform.
- **Testing:** Always test material in the application area before starting full installation.
- **Mixing:** Mix pigment thoroughly with Clear Part A until the color is uniform. Allow color to set for 30 minutes to 24 hours before adding other components. If using pre-pigmented Part A, mix Part A until uniform before combining.
- **Mix ratios:**

PRODUCT	KIT SIZE	PIGMENT PER KIT	LIGHT PIGMENT PER KIT (marked with *)
Polyaspartic 92 Low Odor (EZ or FC)	2 gal (1 gal A + 1 gal B)	4 oz	8 oz
Polyurethane HS (EZ or FC)	1.5 gal (1 gal A + 1/2 gal B)	4 oz	8 oz
Top Shelf® Epoxy (A-Resin + EZ, AP, or FC)	1.5 gal (1 gal A + 1/2 gal B)	4 oz	8 oz
Metallic Epoxy	3 gal (2 gal A + 1 gal B)	4 oz	8 oz

- **Pigment compatibility:** Metallic pigments can be combined with Top Shelf® Epoxy, Polyurethane HS, Polyaspartic 92 Low Odor, and Metallic Epoxy.
- **Application methods:** Final appearance depends on pigment amount, coating thickness, base coat and accent colors, and application technique. The examples below show how the same pigment can produce different effects using various methods:



Back-Rolled Finish



Squeegee Finish



Acetone Spray Pattern



Leaf Blower Texture

- **Prime and base coats:** Choose colors that match or support the desired finish, as they can significantly affect the appearance, depth, and coverage of the metallic coat.
- **UV resistance:** For better color stability, use a clear, UV-resistant product like Polyaspartic or Polyurethane.
- **For custom color:** Complete the Special Order Form (kretus.com/special-order-form). Additional fees and lead times apply.

Disclaimer: This document is intended for Kretus-trained professionals. It is not legally binding and does not remove the user's or specifier's responsibility to ensure materials are used appropriately for the project and jobsite. Always follow the most current industry standards and Kretus technical guidelines. **Note:** Subject to change without notice. For the latest version, visit kretus.com.