

KRETUS®

Safety Data Sheet

SECTION 1: IDENTIFICATION

Product Name: KRETUS® Polyurethane HP, Part B

Recommended Use: For professional use only.

Manufacturer: Kretus, 1055 W. Struck Ave., Orange, CA 92867

Telephone: (714) 694-2061

24 Hour Emergency Telephone Number: (800) 255-3924 (CHEMTEL)

Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

Comments: To the best of our knowledge, this Safety Data Sheet conforms to the requirements of US OSHA 29

CFR1910.1200, 91/155/EEC.

SECTION 2: HAZARD IDENTIFICATION

Emergency Overview: Corrosive. Causes severe burns. Severe respiratory irritant. Severe skin irritant. Severe eye irritant. May cause long-term adverse effects in the aquatic environment.

GHS Classification

Serious Eye Damage; Category 1

Skin Sensitization; Category 1

Chronic Aquatic Toxicity; Category 3



GHS Signal Word: WARNING!

GHS Hazard Statements:

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

Polyurethane HP, Part B SDS, Page 1 of 7

GHS Precautionary Statements:

Prevention:

P261: Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/ physician.

P333 + P313: If skin irritation or rash occurs: Get medical advice/ attention.

Potential Health Effects:

Eye contact: Corrosive to the eyes. Severe eye irritation.

Skin contact: Corrosive to the skin. Harmful in contact with skin. Potential skin sensitizer.

Ingestion: Corrosive and may cause severe and permanent damage to mouth, throat & stomach

Inhalation: May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.

Exposure Guidelines:

Target Organs - Respiratory system, Skin, Eyes.

Symptoms - Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat, headache, dizziness, tiredness, nausea and vomiting.

General Information: This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Prolonged contact may result in chemical burns and permanent damage. Repeated or prolonged contact causes sensitization, asthma and eczemas.

Read the entire SDS for a more thorough evaluation of the hazards.

Storage: Keep container tightly closed and locked in a cool, well-ventilated place.

Disposal: Dispose of contents/container to an approved waste disposal plant in accordance with applicable laws and regulations, and product characteristics at time of disposal.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Concentration (% by Weight)
3-Oxazolidineethanal	CAS 145899-78-1	80-90%
Non-Hazardous	N/A	<10%

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

See Section 11 for Toxicological Information.

SECTION 4: FIRST-AID MEASURES

Polyurethane HP, Part B SDS, Page 2 of 7

General advice

Seek medical advice or medical attention if condition persists.

Contact with Eyes

Rinse immediately with plenty of water for at least 15 minutes.

Contact with Skin

Immediately remove any extraneous chemical, if possible without delay. Take off contaminated clothing and shoes immediately. Wash body off with soap and plenty of water.

Inhalation

Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.

Ingestion

Rinse mouth. Drink plenty of water. Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position and turn victim's head to the side. Do not induce vomiting.

Notes to Physician

No specific treatment. Treat symptomatically. Call the poison control center immediately if large quantities have been ingested. Corticosteroid cream has been effective and treating skin irritation in similar products with similar chemistries.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable extinguishing media: Carbon dioxide (CO2). Foam. Dry chemical. Water Fog.

Specific hazards: May generate ammonia gas. May generate toxic nitrogen oxide gases. Do not allow run-off from firefighting to enter drains or water courses. Incomplete combustion may form carbon monoxide (CO) and nitrogen oxides (NOx). Ammonia gas may be liberated at high temperatures. Burning produces noxious and toxic fumes. Downwind personnel must be evacuated.

Special protective equipment for fire-fighters: Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Danger of Explosion: This product does not present an explosion hazard

Flammable Limits: Not Available Explosion Limits: Not Available Auto-Ignition: 341°C (646°F)

Flash Point: 76°C (169°F) Pensky-Martens Closed Cup

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Polyurethane HP, Part B SDS, Page 3 of 7

Environmental Precautions: Water polluting material. May be harmful to the environment if released in large quantities. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform authorities if the product has caused environmental pollution.

Methods for Cleaning up: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe-Handling

Put on appropriate personal protective equipment, PPE (see Section 8). Eating and drinking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated PPE or clothing, wash hands and face before eating and drinking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Use only in area provided with appropriate exhaust ventilation. Empty containers retain product residue and can be hazardous. Do not get in eyes, skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment.

Conditions for Safe Storage

Store between 4 to 40°C (40 to 104°F) in accordance with local regulations away from sources of heat, ignition, and direct sunlight. Store in original container. Keep in a dry, well-ventilated area, and away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled, unapproved or reactive containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Special Note for Exposure Control: Consult local authorities for acceptable exposure limits.

OSHA PEL (TWA): Not Determined ACGIH TLV (TWA): Not Determined NIOSH REL (TWA): Not Determined

Respiratory protection: In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Eye/face protection: Splash proof safety glasses.

Skin protection: Rubber or plastic apron. Rubber or plastic gloves. Long sleeved clothing or wear protective sleeves. Remove and wash contaminated clothing before re-use.

Other Precautions: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Neoprene gloves. PVC

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating and drinking, smoking or using the lavatory and at the end of the working period. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Environmental exposure controls: Construct a dike to prevent spreading. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Polyurethane HP, Part B SDS, Page 4 of 7

In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Engineering measures: Work in well-ventilated area. Provide natural or explosion-proof fan to ensure adequate ventilation, especially in confined area. Avoid contact with skin, eyes, and clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES	
Appearance	liquid, pale yellow
Odor	sweet
Odor Threshold	No Data Available
рН	Alkaline
Melting/Freezing Point	No Data Available
Initial Boiling Point and Boiling Range	>235°C (>455°F)
Flash Point	170°C
Evaporation Rate	No Data Available
Flammability	No Data Available
Upper/Lower Flammability or Explosive Limits	No Data Available
Auto-ignition Temperature	No Data Available
Vapor Pressure	<20.68 mmHg @ 21°C (71°F)
Vapor Density	No Data Available
Relative Density/Specific Gravity	1.08 g/cm3
Solubility(ies)	Nil

No Data Available

No Data Available

No Data Available

<50 g/L

SECTION 10: STABILITY AND REACTIVITY

VOC (Volatile Organic Compounds)

Partition Coefficient: n-octanol/water

Decomposition Temperature

Viscosity

Chemical stability: Stable under normal conditions. Hazardous reactions will not occur.

Conditions to avoid: Direct source of heat, High moisture. **Materials to avoid:** Strong oxidizers, water, acids and bases.

Contact with water can form highly flammable and explosive vapors.

Hazardous decomposition products: Carbon monoxide (CO). Carbon dioxide(CO2). Ammonia. Aldehydes. Flammable hydrocarbon fragments (e.g., acetylene). Nitrogen oxides (NOx).

Nitrogen oxide can react with water vapors to form corrosive nitric acid.

Hazardous polymerization: Under normal conditions hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity:

Oral: LD50/rat: >2,000 mg/kg

Skin irritation: Rabbit: Corrosive. (Literature data)

Eye irritation: Rabbit: Risk of serious damage to eyes. (OECD Guideline 405) (Literature data) **Sensitization:** Guinea pig: maximization test - sensitizing (OECD Guideline 406) (Literature data)

Polyurethane HP, Part B SDS, Page 5 of 7

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity Effects:

LC50/96 hours Fish	87.5 mg/L
EC50/48 hours Daphnia	>100mg/L
EbC50 Algal growth inhibition	21mg/L
IC50/3 hours Microbial growth inhibition	>1000mg/L

No environmental hazard is anticipated provided that the material is handled and disposed of with due care and attention.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste should be disposed of according to local, state, and federal regulations. Chemical residues are generally classified as special waste, and as such are covered by regulations which vary according to location. Contact your local waste disposal authority for advice or pass to a chemical disposal company. Dispose of containers with care.

SECTION 14: TRANSPORT INFORMATION

	UN Number	UN Proper Shipping Name	Transport Hazard Class(es)	Packing Group	Environmental Hazards
DOT	*Not Regulated	<119gallon, Not Regulated	*Not Regulated	*Not Regulated	Not Regulated
IMO/IMDG	*Not Regulated	*Not Regulated	*Not Regulated	*Not Regulated	Not Regulated
IATA/CAO	*Not Regulated	*Not Regulated	*Not Regulated	*Not Regulated	Not Regulated

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code.

SECTION 15: REGULATORY INFORMATION

Country	Regulatory List	Notification
USA	TSCA	Included on Inventory
EU	EINECS	Included on Inventory
Canada	DSL	Included on Inventory
China	SEPA	Included on Inventory
Japan	ENCS	Included on Inventory

OSHA: This product is considered to be a hazardous chemical under 29 CFR 1910.1200.

SARA Section 311 AND 312 - This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories: IMMEDIATE HEALTH HAZARD

SARA Section 313 - This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: None

Polyurethane HP, Part B SDS, Page 6 of 7

California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) - This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

Canadian WHMIS - Class E: Corrosive material, D2B: Toxic material causing other toxic effects.

This product has been classified in accordance with the hazard criteria of the Controlled Products

Regulations and the SDS contain all the information required by the Controlled Products Regulations.

SECTION 16: OTHER INFORMATION

Hazardous Material Information System (HMIS):

Scale 0-4		NFPA	HMIS	
4-Severe Hazard	Health	1	1	
3-Serious Hazard	Flammability	2	2	
2-Moderate Hazard	Reactivity	1	1	
1-Slight Hazard				
0-Minimal Hazard				

Personal Protection: Safety goggles, neoprene rubber gloves, vapor respirator

Prepared by: Kretus, Inc.

Disclaimer: The information and recommendations presented herein are accurate to the best of our knowledge. User must conduct their own tests to determine the suitability of these products for their particular purposes and usage. Because of numerous factors affecting results, KRETUS® Inc and its affiliation makes no warranty of any kind, express or implied, including those of merchantability and fitness for purpose, other than material conforms to our applicable current specifications. KRETUS® Inc assumes no legal responsibility for use or reliance on the information contained in this safety data sheet

Polyurethane HP, Part B SDS, Page 7 of 7 Rev: 05/05/24