THOUGHTFULLY DESIGNED CONCRETE COATINGS

## **Color Chart**

# **TOP SHELF® EPOXY & COLORANT PACKS**

Combine KRETUS Top Shelf<sup>®</sup> Epoxy Colorant with clear Top Shelf<sup>®</sup> Epoxy. Colors also come pre-blended in select Top Shelf<sup>®</sup> Epoxy resins (Part A).



Colors shown are approximate. Resin and hardener selection, substrate, mix ratio, application technique, ambient temperature, and relative humidity may affect color. Colors sold as pre-blended base and as colorant packs. To order custom color, fill out KRETUS® Special Order form available at kretus. com/project-planning. Additional fees apply. UV Resistance: All epoxy will amber over time. If color stability is important: Use a UV-resistant system, such as Polyaspartic or Polyurethane. If adding a UV-resistant top coat for color stability, the top coat must be opaque and pigmented.

kretus.com

KRĒTUS

## GENERAL MIXING GUIDE

### **Ensuring Uniform Color**

Check that product batch numbers are the same. Different batch numbers can produce slight variance in color. If different batch numbers, box product together and blend thoroughly before mixing product with other components. Always test application on site.

To ensure color opacity, apply two coats of White, Safety Red, and Safety Yellow.

### **Mixing Application**

Premeasure components before combining. Add Colorant to Part A and mix for 1-2 minutes or until color is uniform. Add Part B and mix for 1-2 minutes. Total mixing time = 3 minutes.

#### **Mixing Ratio**

PRODUCT	KIT SIZE	COLORANT	MIX RRATIO (A:B:COLOR)
TOP SHELF <sup>®</sup> EPOXY	1.5 gal	16 oz	1 gal:1/2 gal:16 oz
	15 gal	1 gal, 32 oz	10 gal:5 gal:1 gal, 32 oz
	150 gal	12 gal, 64 oz	100 gal:50 gal:12 gal, 64 oz

DISCLAIMER: The information contained in this document is intended for use by KRETUS<sup>®</sup> qualified and trained professionals. This is not a legally binding document and does not release the specifier from their responsibility to apply materials correctly under the specific conditions of the construction site and the intended results of the construction process. The most current valid standards for testing and installation, acknowledged rules of technology, as well as KRETUS<sup>®</sup> technical guidelines must be adhered to at all times. The steps given in this document and other mentioned documents are critical to the success of your project.

KRĒTUS